

Delivery program PN10, Length F5

Main Performance Specification

Nominal Pressure in PN		10
Test pressure in PN	Intensity	15
	Sealing (hydraulic test)	11
	Sealing (air test)	6
Applicable medium	Water, sewage	
Working temperature in °C		< 80°C

Main Accessory Material

Body	GGG 50 ductile iron
Cover	GGG 50 ductile iron
Wedge	Ductile iron + NBR/EPDM
Stem	AISI 316
Stem nuts	Cast bronze
Stop bearing	Cast bronze
Sealing ring	NBR/EPDM

DN	L	D	D1	D2	b	A x B	H1	H	K	Weight in Kg
500	700	670	630	582	26,5	705 x 363	1048	1398	1255	620
600	800	760	725	682	30	868 x 408	1208	1588	1455	870
700	900	855	865	797	32,5	1038 x 413	1390	1750	1655	1170
800	1000	1015	950	904	35	1182 x 471	1594	1958	1912	1750
900	1100	1115	1050	1004	37,5	1342 x 612	1594	1958	1981	1870
1000	1200	1230	1150	1111	40	1492 x 678	1800	2265	2251	3200
1200	1400	1455	1380	1329	45	1898 x 700	2270	2695	2510	5900

all measurements in mm

